



arclite

# 28003603

28003603

GTIN: 9006210751658

TRIDONIC LED Treiber Konstantstrom LC 60/150-550/230 o4a NF h16 EXC4 28003603

## ARTIKELDETAILS

Dimmable constant-current LED driver for luminaire installation, Dimming range from 1 - 100 %, For luminaires of protection class I and protection class II, Output current adjustable between 150 - 550 mA, Max. output power 60 W, Up to 94 % efficiency, Power consumption in stand-by < 14 W, Nominal life up to 100.000 h, 5-year guarantee, "Low profile" metal housing with white upper part, Housing height only 16 mm, Protection class IP20, Near field communication (NFC), one4all (DALI-2 DT 6, DSI, switchDIM, corridorFUNCTION), Terminals: 0° plug-in terminals, Adjustable output current in 1 mA steps (NFC, DALI), Complies with DALI-2 parts: 251 (luminaire data), 252 (energy report) and 253 (diagnosis & maintenance), Constant light output function (eCLO), Power-up fading for AC, Driver switch-off via fade2zero, Protection functions (overtemperature, short-circuit, overload, open-circuit), Suitable for safety lighting systems according to EN 50172, Flexible configuration via companionSUITE, Supports NFC multiple programming (whole cardboard unit), Application-oriented operating window for max. Compatibility, High energy savings due to low stand-by losses and high efficiency, Lifetime up to 100,000 h and 5-year warranty, For linear and area lighting in office applications.

## EIGENSCHAFTEN

## MERKMALE

Produktgruppe	LED-Betriebsgerät (EC002710)
Kompatibel mit Apple HomeKit	Nein
Kompatibel mit Google Assistant	Nein
Kompatibel mit Amazon Alexa	Nein
IFTTT-Unterstützung verfügbar	Nein
Ohne Dimmfunktion	Ja
Ausgangsspannung	0 V
Ausgangsstrom	150 - 550 mA
Geeignet für Gleichspannung (Primärseite)	Ja
Ausgangsleistung	34,500 - 60,000 W
Schutzart (IP)	IP20
Länge	280 mm
Breite	30,00 mm
Höhe	16,00 mm

## IMPORT/EXPORT

Statistische Warennummer	Gleichrichter (85044083)
--------------------------	--------------------------

## SONSTIGES

REACH Indicator	Ja
-----------------	----